

Type	Spleten	Breedte extern	Hoogte extern	Diepte extern	Breedte inwendig	Hoogte inwendig	Diepte inwendig	Afgeronde waarde		
								Flow	Flow	Flow
								< 20 Pa	< 30 Pa	< 40 Pa
Dice-05	5	1200	1060	1250	1060	990	650	2550	3150	3600
Dice-07	7	1200	1420	1250	1060	1350	650	3600	4400	5100
Dice-07-L	7	1400	1420	1400	1260	1350	800	4250	5200	6000
Dice-07-XL	7	1600	1420	1500	1460	1350	900	4900	6000	6900
Dice-09	9	1200	1740	1250	1060	1670	650	4600	5650	6500
Dice-09-L	9	1400	1740	1400	1260	1670	800	5450	6700	7700
Dice-09-XL	9	1600	1740	1500	1460	1670	900	6300	7700	8900

Interne diepte omkasting = unit diepte + 200 afblaas + 100 aanzuig is advies.

advies: 300 minimum: 250

Interne hoogte omkasting = unit hoogte + trillingsdempers + opstelhoogte + 100 mm is advies

advies: 100 minimum: 50

Interne breedte omkasting = unit breedte + 100 + 100 ivm aansluiting is advies

advies: 200 minimum: 150